

Scripting Languages

Higher-level languages.
More compact for small programs.
Often not suitable for large systems.
The more popular ones:

Awk
Perl
Python
Tcl
Bourne Shell

Scripting Languages

COMS W4115
Prof. Stephen A. Edwards
Fall 2007
Columbia University
Department of Computer Science

Simple Awk Program

Input file. Each line a record. Space-separated fields:
employee, pay rate, hours worked

```
Beth 10.0 0
Dan 9.75 0
Kathy 14.0 10
Mark 10.0 20
Susie 8.25 18
```

Run on the awk program

```
$3 > 0 { print $1, $2 * $3 }
```

produces

```
Kathy 140
Mark 200
Susie 148.5
```

Simple Awk Program

```
Beth 10.0 0
Kathy 14.0 10
```

3rd field

```
{ $3 > 0 { print $1, $2 * $3 }
```

action

Kathy 140

Awk Program Structure

```
pattern { action }
pattern { action }
:
```

awk scans an input file one line at a time and, in order, runs each action whose pattern matches.

Patterns:

BEGIN, END True before and after the file.
expression Condition
/regular expression/ String pattern match
pattern && pattern String pattern match
pattern || pattern Boolean operators
! pattern

Awk

Named for its three developers:

Alfred Aho
Peter Weinberger
Brian Kernighan

Good for data file manipulation. I use it for computing grades and other simple tasks.

Awk One-Liners

Print every line

```
{ print }
```

Print the first and third fields of each line

```
{ print $1, $3 }
```

Print every line with three fields

```
NF == 3 { print }
```

Print a line number before every line

```
{ print NR, $0 }
```

Statistics in Awk

```
#!/bin/awk -f
BEGIN { n = 0; s = 0; ss = 0; }
NF == 1 { n++; s += $1; ss += $1 * $1; }
END {
    print n " data points"
    m = (s+0.0) / n; print m " average"
    sd = sqrt( (ss - n * m * m) / ( n - 1.0) )
    print sd " standard deviation"
}
```

```
Run on 1 10 6 data points
        5 5 6.16667 average
        3 7 3.92003 standard deviation
        7 11
```

Associative Arrays: Word Counter

```
{ gsub(/[.,:;!(){}]/, "") # remove punctuation
  for ( i = 1; i <= NF; i++ )
    count[$i]++
}
END { for (w in count)
      print count[w], w | "sort -rn"
}
```

Run on the Tiger reference manual produces

```
103 the
58 of
51 is
49 and
49 a
35 expression
32 The
29 =
```

Perl

Larry Wall's
Practical Extraction and Report Language
or
Pathologically Eclectic Rubbish Lister

Larger, more flexible language than Awk. Good for text processing and other tasks. Strange semantics. Heinous syntax.

Excellent regular-expression support. More complicated data structures possible (even classes).

Wordcount in Perl

```
#!/usr/bin/perl
while(<>) {
    chop;
    s/[.,:;!(){}]/ /g;
    @words = split;
    foreach (@words) {
        $count{$_}++;
    }
    open(SORTER, "| sort -nr");
    foreach (keys %count) {
        print SORTER
            $count{$_}, " ", $_, "\n";
    }
}
```

Understandable wordcount in Perl

```
#!/usr/bin/perl
while($line = <>) {
    chop($line);
    $line =~ s/[.,:;!(){}]/ /g;
    @words = split(/\s+/, $line);
    foreach $word (@words) {
        $count{$word}++;
    }
}
open(SORTER, "| sort -nr");
foreach $word (keys %count) {
    print SORTER
        $count{$word}, " ", $word, "\n";
}
```

“There’s more than one way to do it”

Perhaps too many. Equivalent ways to print STDIN:

```
while (<STDIN>) { print; }
print while <STDIN>
print while <>
while (defined($_ = <STDIN>)) { print $_; }
for (<STDIN>;) { print; }
print $_ while defined($_ = <STDIN>);
```

Many Perl statements come in prefix and postfix form

```
while (...) ...
... while ...
if (...) ...
... if ...
... unless ...
```

So Why Perl?

Perhaps the most popular scripting language.

Despite its flaws, it’s very powerful.

Almost has a good type system.

Very few things *can’t* be done in Perl.

Fast, flexible interpreter.

Ability to make virtually every Unix system call. Binary data manipulation.

Ported everywhere.

Very, very extensive collection of libraries. Database access. CGI/HTML for the web. Math. IPC. Time.

Python

Perl designed by a sane man.

Very clean syntax and semantics.

Large collection of libraries (but not as big as Perl’s).

Regular expression support (but not as integrated as Perl’s).

Wordcount in Python

```
#!/usr/bin/env python
import fileinput, re, string, os

count = {}
for line in fileinput.input():
    line = re.sub(r'[.,:;!(){}]', "", line)
    for word in string.split(line):
        if not count.has_key(word):
            count[word] = 1
        else:
            count[word] = count[word] + 1

f = os.popen("sort -nr", 'w')
for word in count.keys():
    f.write('%d %s\n' % (count[word], word))
```

Python Classes

```
class Complex:
    def __init__(self, realpart, imagpart):
        self.r = realpart
        self.i = imagpart

    def add(self, a):
        self.r = self.r + a.r
        self.i = self.i + a.i

    def p(self):
        print "%g + %gi" % (self.r, self.i)

x = Complex(1,2)
y = Complex(2,3)
x.p()
x.add(y)
x.p()

Prints
1 + 2i
3 + 5i
```

Python’s Merits

Good support for programming-in-the-large:

Packages with separate namespaces; Exceptions; Classes

Persistent datastructures (pickling)

High-level: lists, strings, associative arrays, iterators
Good collection of libraries:

Operating-system access (files, directories, etc.);
String manipulation; Curses; Databases; Networking
(CGI, HTTP, URL, mail/Mime, HTML); Tk;
Cryptography, System-specific (Windows, Mac, SGI, POSIX)

Python vs. Perl

Python can be the more verbose language, but Perl can be cryptic.

Regular expression support more integrated with language in Perl.

Perl better-known.

Probably comparable execution speeds.

More "tricks" possible in Perl; Python more disciplined.

Python has the much cleaner syntax and semantics; I know which language's programs I'd rather maintain.

Tcl

John Ousterhout's Tool Command Language was originally intended to be grafted on to an application to make it controllable.

Since become a general-purpose scripting language. Its syntax is quite simple, although rather atypical for a programming language.

Tk, a Tcl package, provide graphical user interface widgets. Tcl/Tk may be the easiest way to write a GUI.

Tk has been connected to Perl and Python as well.

Tcl Syntax

Shell-like command syntax:

command argument argument ...

All data is strings (incl. numbers and lists)

Macro-like variable substitution:

```
set foo "123 abc"  
bar 1 $foo 3
```

Command substitution:

```
set foo 1  
set bar 2  
puts [eval $foo + $bar]; # Print 3
```

Nifty Tcl Features

Associative arrays

```
set count(stephen) 1
```

Lists

```
lappend foo 1  
lappend foo 2  
foreach i $foo { puts $i } ; # print 1 then 2
```

Procedures

```
proc sum3 {a b c} {  
    return [expr $a + $b + $c]  
}
```

Wordcount in Tcl

```
#!/usr/bin/env tclsh
```

```
while {[gets stdin line] >= 0} {  
    regsub -all {[.:;!(){}]} $line "" line  
    foreach word $line {  
        if {[info exists count($word)]} {  
            set count($word) 1  
        } else {  
            incr count($word)  
        }  
    }  
}
```

```
set f [open "| sort -rn" w]  
foreach word [array names count] {  
    puts $f "$count($word) $word"  
}
```


Tk

"Hello World" in Tk.


```
button .b -text "Hello World" -command "exit"  
pack .b
```



An Editable Graph



An Editable Graph



```
# Set up the main window  
set w .plot  
catch destroy $w  
toplevel $w  
wm title $w "Plot Demonstration"  
wm icontame $w "Plot"  
positionWindow $w  
set c $w.c
```

```
# Text description at top  
label $w.msg -font $font -wraplength 4i -justify left \  
-text "This window displays a canvas widget containing  
a simple 2-dimensional plot. You can doctor the data  
by dragging any of the points with mouse button 1."  
pack $w.msg -side top
```

An Editable Graph

```
# Set up bottom control buttons  
frame $w.buttons -side bottom -fill x -pady 2m  
button $w.buttons.dismiss -text Dismiss -command "destroy$w"  
button $w.buttons.code -text "See Code" -command "showCode$w"  
pack $w.buttons.dismiss $w.buttons.code -side left -expand 1
```

```
# Set up graph itself  
canvas $c -relief raised -width 450 -height 300  
pack $w.c -side top -fill x
```

```
# Draw axes  
set plotFont Helvetica 18  
$c create line 100 250 400 250 -width 2  
$c create line 100 250 100 50 -width 2  
$c create text 225 20 -text "A Simple Plot" -font $plotFont \  
-fill brown
```

An Editable Graph

```
# Draw axis labels
for {set i 0} {$i <= 10} {incr i} {
  set x [expr {100 + ($i*30)}]
  set y [expr {100 + ($i*30)}]
  set create_line $x 250 $y 245 -width 2
  set create_text $x 254 -text [expr 100+$i] \
    -anchor n -font $plotFont
}
for {set i 0} {$i <= 5} {incr i} {
  set y [expr {250 - ($i*40)}]
  set create_line 100 $y 105 $y -width 2
  set create_text 96 $y -text [expr $i501.0] \
    -anchor e -font $plotFont
}
# Draw points
foreach point {{12 56} {20 94} {33 98} {32 120} {61 180}
              {75 160} {98 223}} {
  set x [expr {100 + ($[lindex $point 0])}]
  set y [expr {250 - ($[lindex $point 1])}]
  set item [$c create oval [expr $x-6] [expr $y-6] \
    -fill skyblue2]
  set addtag point withtag $item
}
```

cc in sh

```
#!/bin/sh

# Set up command names
root=/usr/lib
cpp=$root/cpp
cc1=$root/cc1
as=/usr/bin/as
ld=/usr/bin/ld

# Complaint function
usage() {
  echo "usage: $0 [options] files ..." 1>&2
  exit 1
}

# Default output filename
outfile="a.out"
```

cc in sh

```
# Preprocess and compile to assembly
for file in $files; do
  asmfile=`echo $file | sed s/\.c$/\.s/`
  $cpp $file | $cc1 > $asmfile
  $as -o $objfile $asmfile
done
if [ "$stopaftercompile" ]; then exit 0; fi

# Assemble object files
for file in $files; do
  objfile=`echo $file | sed s/\.s$/\.o/`
  $as -o $objfile $file
done
ofiles="$ofiles $objfile"
if [ "$stopafterassemble" ]; then exit 0; fi

# Link to build executable
$ld -o $outfile $ofiles
exit 0
```

An Editable Graph

```
# Bind actions to events
set bind_point <Any-Enter> "$c itemconfig current -fill red"
set bind_point <Any-Leave> "$c itemconfig current -fill skyblue2"
set bind_point <l> "plotDown $c %x %y"
set bind_point <ButtonRelease-1> "$c dtag selected"
bind $c <B1-Motion> "plotMove $c %x %y"

set plot(lastX) 0
set plot(lastY) 0
proc plotDown {w x y} { # Called when point clicked
  global plot
  $w addtag selected withtag current
  $w raise current
  set plot(lastX) $x
  set plot(lastY) $y
}
proc plotMove {w x y} { # Called when point dragged
  global plot
  $w move selected [expr $x-$plot(lastX)] \
    [expr $y-$plot(lastY)]
  set plot(lastX) $x
  set plot(lastY) $y
}
```

cc in sh

```
# Parse command-line options
while { ! -z "$1" }; do
  case x"$1" in
    x-v) echo "Stephen's cc 1.0"; exit 0 ;;
    x-o) shift; outfile=$1 ;;
    x-c) stopafterassemble=1 ;;
    x-s) stopaftercompile=1 ;;
    x-E) stopafterpreprocess=1 ;;
    x-*) echo "Unknown option $1" 1>&2; usage ;;
    *) break ;;
  esac
  shift
done

# Initialize lists of files to process
cfiles=""
sfiles=""
ofiles="crtl.o"

if [ $# = 0 ]; then
  echo "$0: No input files" 1>&2; exit 1
fi
```

Bourne Shell

Default shell on most Unix systems (sh or bash).
Good for writing "shell scripts." parsing command-line arguments, invoking and controlling other commands, etc.
Example: The cc command.

Most C compilers built from four pieces:

- Preprocessor (cpp)
- Actual compiler (cc1)
- Assembler (as)
- Linker (ld)

cc in sh

```
# Parse filenames
while { ! -z "$1" }; do
  case x"$1" in
    x*.c) cfiles="$cfiles $1" ;;
    x*.s) sfiles="$sfiles $1" ;;
    x*.o | x*.a) ofiles="$ofiles $1" ;;
    *) echo "Unrecognized file type $1" 1>&2; exit 1 ;;
  esac
  shift
done

# Run preprocessor standalone
if [ "$stopafterpreprocess" ]; then
  for file in $cfiles; do
    $cpp $file
  done
  exit 0
fi
```

What To Use When

awk: Best for simple text-processing (file of fields)
Perl: Best for legacy things, things requiring regexps
Python: Best all-around, especially for large programs
Tcl: Best for command languages, GUIs
sh: Best for portable "invoking" scripts

Scripting Languages Compared

	awk	Perl	Python	Tcl	sh
Shell-like	N	N	Y	Y	Y
Reg. Exp.	B	A	C	C	D
Types	C	B	A	B	D
Structure	C	B	A	B	C
Syntax	B	F	A	B	C
Semantics	A	C	A	B	B
Speed	B	A	A	B	C
Libraries	C	A	A	B	C
Power	B	A	A	B	C
Verbosity	B	A	C	C	B